


<p>Product Features</p> <ul style="list-style-type: none"> - Reusable - Vibration Proof - Chemical Resistant - Usable Temperature Minus 50°F to 570°F - Locks in Full 360° Rotation 	 <p>NOTHING PERFORMS BETTER</p> <p>999 Forest Edge Drive Vernon Hills, IL 60061 847-970-4050 www.securitylocknut.com</p>	<h3>1 1/8 X 7 Heavy Hex</h3>		
<p>Product Specifications</p> <ul style="list-style-type: none"> - Prevailing Torque- IFI- 100/107 standard - Material Properties - SAE J995 / ASTM A563 - Dimensional - ANSI/ASME B.18.2.2.2; 2012 - Threads - Class 2B (UNC & UNF) 		<p>Wt/100: 60.2 Lbs</p>	<p>Grade Code (G) 1 = Grade 5 2 = Grade 8</p>	<p>Plating Code (P) 0 = No Plating 2 = Zinc Dichromate (ZDC) 5 = ATD (Lock Only) 6 = ATD (Nut Body and Lock) 7 = ZDC Nut Body / ATD Lock</p>
<p>SCALE: 1.0</p>		<p>UNITS: INCHES</p>	<p>PART NUMBER</p>	
<p>REV: A</p>		<p>1001-1125-070-G-P</p>	<p>BODY STYLE</p>	<p>THREAD SIZE (x 0.001)</p>
<p>DATE: JAN 06, 2014</p>		<p>PITCH (x 0.01)</p>	<p>GRADE CODE</p>	<p>PLATING CODE</p>