



<p><b>Product Features</b></p> <ul style="list-style-type: none"> <li>- Reusable</li> <li>- Vibration Proof</li> <li>- Chemical Resistant</li> <li>- Usable Temperature Minus 50°F to 570°F</li> <li>- Locks in Full 360° Rotation</li> </ul>	 <p><b>NOTHING PERFORMS BETTER</b></p>	<h3>1 1/4 X 7 Heavy Hex</h3>		
<p><b>Product Specifications</b></p> <ul style="list-style-type: none"> <li>- Prevailing Torque- IFI- 100/107 standard</li> <li>- Material Properties - SAE J995 / ASTM A563</li> <li>- Dimensional - ANSI/ASME B.18.2.2.2; 2012</li> <li>- Threads - Class 2B (UNC &amp; UNF)</li> </ul>		<p>999 Forest Edge Drive          Vernon Hills, IL 60061          847-970-4050  <a href="http://www.securitylocknut.com">www.securitylocknut.com</a></p>	<p>Wt/100: 79.7 Lbs</p>	<p>Grade Code <b>(G)</b>          1 = Grade 5          2 = Grade 8</p>
<p>SCALE: 1.0</p> <p>UNITS: INCHES</p>			<p><b>PART NUMBER</b>  <b>1001-1250-070-G-P</b></p>	<p>REV: A</p>
<p>DATE: JAN 06, 2014</p>				